

---

## **Secure Access**

## **Client-side Changes Guide**



**Instant Virtual Extranet Platform**

---





**Secure Access**

## **Client-side Changes Guide**

*Release 5.5*

**Juniper Networks, Inc.**  
1194 North Mathilda Avenue  
Sunnyvale, CA 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

This product includes the Envoy SNMP Engine, developed by Epilogue Technology, an Integrated Systems Company. Copyright © 1986–1997, Epilogue Technology Corporation. All rights reserved. This program and its documentation were developed at private expense, and no part of them is in the public domain.

This product includes memory allocation software developed by Mark Moraes, copyright © 1988, 1989, 1993, University of Toronto.

This product includes FreeBSD software developed by the University of California, Berkeley, and its contributors. All of the documentation and software included in the 4.4BSD and 4.4BSD-Lite Releases is copyrighted by The Regents of the University of California. Copyright © 1979, 1980, 1983, 1986, 1988, 1989, 1991, 1992, 1993, 1994. The Regents of the University of California. All rights reserved.

GateD software copyright © 1995, The Regents of the University. All rights reserved. Gate Daemon was originated and developed through release 3.0 by Cornell University and its collaborators. Gated is based on Kirton's EGP, UC Berkeley's routing daemon (routed), and DCN's HELLO routing protocol. Development of Gated has been supported in part by the National Science Foundation. Portions of the GateD software copyright © 1988, Regents of the University of California. All rights reserved. Portions of the GateD software copyright © 1991, D. L. S. Associates.

Juniper Networks, the Juniper Networks logo, NetScreen, NetScreen Technologies, the NetScreen logo, NetScreen-Global Pro, ScreenOS, and GigaScreen are registered trademarks of Juniper Networks, Inc. in the United States and other countries.

The following are trademarks of Juniper Networks, Inc.: ERX, E-series, ESP, Instant Virtual Extranet, Internet Processor, J2300, J4300, J6300, J-Protect, J-series, J-Web, JUNOS, JUNOScope, JUNOScript, JUNOSe, M5, M7i, M10, M10i, M20, M40, M40e, M160, M320, M-series, MMD, NetScreen-5GT, NetScreen-5XP, NetScreen-5XT, NetScreen-25, NetScreen-50, NetScreen-204, NetScreen-208, NetScreen-500, NetScreen-5200, NetScreen-5400, NetScreen-IDP 10, NetScreen-IDP 100, NetScreen-IDP 500, NetScreen-Remote Security Client, NetScreen-Remote VPN Client, NetScreen-SA 1000 Series, NetScreen-SA 3000 Series, NetScreen-SA 5000 Series, NetScreen-SA Central Manager, NetScreen Secure Access, NetScreen-SM 3000, NetScreen-Security Manager, NMC-RX, SDX, Stateful Signature, T320, T640, T-series, and TX Matrix. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners. All specifications are subject to change without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

Copyright © 2006, Juniper Networks, Inc.  
All rights reserved. Printed in USA.

*Juniper Networks Secure Access Client-side Changes Guide*, Release 5.5  
Writer: Claudette Hobbart, Paul Battaglia, Gary Beichler  
Editor: Mark Smallwood  
Covers design: Edmonds Design

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

#### Year 2000 Notice

Juniper Networks hardware and software products are Year 2000 compliant. The JUNOS software has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### Software License

The terms and conditions for using this software are described in the software license contained in the acknowledgment to your purchase order or, to the extent applicable, to any reseller agreement or end-user purchase agreement executed between you and Juniper Networks. By using this software, you indicate that you understand and agree to be bound by those terms and conditions.

Generally speaking, the software license restricts the manner in which you are permitted to use the software and may contain prohibitions against certain uses. The software license may state conditions under which the license is automatically terminated. You should consult the license for further details.

For complete product documentation, please see the Juniper Networks Web site at [www.juniper.net/techpubs](http://www.juniper.net/techpubs).

#### End User License Agreement

**READ THIS END USER LICENSE AGREEMENT ("AGREEMENT") BEFORE DOWNLOADING, INSTALLING, OR USING THE SOFTWARE. BY DOWNLOADING, INSTALLING, OR USING THE SOFTWARE OR OTHERWISE EXPRESSING YOUR AGREEMENT TO THE TERMS CONTAINED HEREIN, YOU (AS CUSTOMER OR IF YOU ARE NOT THE CUSTOMER, AS A REPRESENTATIVE/AGENT AUTHORIZED TO BIND THE CUSTOMER) CONSENT TO BE BOUND BY THIS AGREEMENT. IF YOU DO NOT OR CANNOT AGREE TO THE TERMS CONTAINED HEREIN, THEN (A) DO NOT DOWNLOAD, INSTALL, OR USE THE SOFTWARE, AND (B) YOU MAY CONTACT JUNIPER NETWORKS REGARDING LICENSE TERMS.**

- 1. The Parties.** The parties to this Agreement are Juniper Networks, Inc. and its subsidiaries (collectively "Juniper"), and the person or organization that originally purchased from Juniper or an authorized Juniper reseller the applicable license(s) for use of the Software ("Customer") (collectively, the "Parties").
- 2. The Software.** In this Agreement, "Software" means the program modules and features of the Juniper or Juniper-supplied software, and updates and releases of such software, for which Customer has paid the applicable license or support fees to Juniper or an authorized Juniper reseller.
- 3. License Grant.** Subject to payment of the applicable fees and the limitations and restrictions set forth herein, Juniper grants to Customer a non-exclusive and non-transferable license, without right to sublicense, to use the Software, in executable form only, subject to the following use restrictions:
  - Customer shall use the Software solely as embedded in, and for execution on, Juniper equipment originally purchased by Customer from Juniper or an authorized Juniper reseller, unless the applicable Juniper documentation expressly permits installation on non-Juniper equipment.
  - Customer shall use the Software on a single hardware chassis having a single processing unit, or as many chassis or processing units for which Customer has paid the applicable license fees.
  - Product purchase documents, paper or electronic user documentation, and/or the particular licenses purchased by Customer may specify limits to Customer's use of the Software. Such limits may restrict use to a maximum number of seats, registered endpoints, concurrent users, sessions, calls, connections, subscribers, clusters, nodes, or transactions, or require the purchase of separate licenses to use particular features, functionalities, services, applications, operations, or capabilities, or provide throughput, performance, configuration, bandwidth, interface, processing, temporal, or geographical limits. Customer's use of the Software shall be subject to all such limitations and purchase of all applicable licenses.

The foregoing license is not transferable or assignable by Customer. No license is granted herein to any user who did not originally purchase the applicable license(s) for the Software from Juniper or an authorized Juniper reseller.

**4. Use Prohibitions.** Notwithstanding the foregoing, the license provided herein does not permit the Customer to, and Customer agrees not to and shall not: (a) modify, unbundle, reverse engineer, or create derivative works based on the Software; (b) make unauthorized copies of the Software (except as necessary for backup purposes); (c) rent, sell, transfer, or grant any rights in and to any copy of the Software, in any form, to any third party; (d) remove any proprietary notices, labels, or marks on or in any copy of the Software or any product in which the Software is embedded; (e) distribute any copy of the Software to any third party, including as may be embedded in Juniper equipment sold in the secondhand market; (f) use any 'locked' or key-restricted feature, function, service, application, operation, or capability without first purchasing the applicable license(s) and obtaining a valid key from Juniper, even if such feature, function, service, application, operation, or capability is enabled without a key; (g) distribute any key for the Software provided by Juniper to any third party; (h) use the Software in any manner that extends or is broader than the uses purchased by Customer from Juniper or an authorized Juniper reseller; (i) use the Software on non-Juniper equipment where the Juniper documentation does not expressly permit installation on non-Juniper equipment; (j) use the Software (or make it available for use) on Juniper equipment that the Customer did not originally purchase from Juniper or an authorized Juniper reseller; or (k) use the Software in any manner other than as expressly provided herein.

**5. Audit.** Customer shall maintain accurate records as necessary to verify compliance with this Agreement. Upon request by Juniper, Customer shall furnish such records to Juniper and certify its compliance with this Agreement.

**6. Confidentiality.** The Parties agree that aspects of the Software and associated documentation are the confidential property of Juniper. As such, Customer shall exercise all reasonable commercial efforts to maintain the Software and associated documentation in confidence, which at a minimum includes restricting access to the Software to Customer employees and contractors having a need to use the Software for Customer's internal business purposes.

**7. Ownership.** Juniper and Juniper's licensors, respectively, retain ownership of all right, title, and interest (including copyright) in and to the Software, associated documentation, and all copies of the Software. Nothing in this Agreement constitutes a transfer or conveyance of any right, title, or interest in the Software or associated documentation, or a sale of the Software, associated documentation, or copies of the Software.

**8. Warranty, Limitation of Liability, Disclaimer of Warranty.** The warranty applicable to the Software shall be as set forth in the warranty statement that accompanies the Software (the "Warranty Statement"). Nothing in this Agreement shall give rise to any obligation to support the Software. Support services may be purchased separately. Any such support shall be governed by a separate, written support services agreement. TO THE MAXIMUM EXTENT PERMITTED BY LAW, JUNIPER SHALL NOT BE LIABLE FOR ANY LOST PROFITS, LOSS OF DATA, OR COSTS OR PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR FOR ANY SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, THE SOFTWARE, OR ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. IN NO EVENT SHALL JUNIPER BE LIABLE FOR DAMAGES ARISING FROM UNAUTHORIZED OR IMPROPER USE OF ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. EXCEPT AS EXPRESSLY PROVIDED IN THE WARRANTY STATEMENT TO THE EXTENT PERMITTED BY LAW, JUNIPER DISCLAIMS ANY AND ALL WARRANTIES IN AND TO THE SOFTWARE (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. IN NO EVENT DOES JUNIPER WARRANT THAT THE SOFTWARE, OR ANY EQUIPMENT OR NETWORK RUNNING THE SOFTWARE, WILL OPERATE WITHOUT ERROR OR INTERRUPTION, OR WILL BE FREE OF VULNERABILITY TO INTRUSION OR ATTACK. In no event shall Juniper's or its suppliers' or licensors' liability to Customer, whether in contract, tort (including negligence), breach of warranty, or otherwise, exceed the price paid by Customer for the Software that gave rise to the claim, or if the Software is embedded in another Juniper product, the price paid by Customer for such other product. Customer acknowledges and agrees that Juniper has set its prices and entered into this Agreement in reliance upon the disclaimers of warranty and the limitations of liability set forth herein, that the same reflect an allocation of risk between the Parties (including the risk that a contract remedy may fail of its essential purpose and cause consequential loss), and that the same form an essential basis of the bargain between the Parties.

**9. Termination.** Any breach of this Agreement or failure by Customer to pay any applicable fees due shall result in automatic termination of the license granted herein. Upon such termination, Customer shall destroy or return to Juniper all copies of the Software and related documentation in Customer's possession or control.

**10. Taxes.** All license fees for the Software are exclusive of taxes, withholdings, duties, or levies (collectively "Taxes"). Customer shall be responsible for paying Taxes arising from the purchase of the license, or importation or use of the Software.

**11. Export.** Customer agrees to comply with all applicable export laws and restrictions and regulations of any United States and any applicable foreign agency or authority, and not to export or re-export the Software or any direct product thereof in violation of any such restrictions, laws or regulations, or without all necessary approvals. Customer shall be liable for any such violations. The version of the Software supplied to Customer may contain encryption or other capabilities restricting Customer's ability to export the Software without an export license.

**12. Commercial Computer Software.** The Software is "commercial computer software" and is provided with restricted rights. Use, duplication, or disclosure by the United States government is subject to restrictions set forth in this Agreement and as provided in DFARS 227.7201 through 227.7202-4, FAR 12.212, FAR 27.405(b)(2), FAR 52.227-19, or FAR 52.227-14(ALT III) as applicable.

**13. Interface Information.** To the extent required by applicable law, and at Customer's written request, Juniper shall provide Customer with the interface information needed to achieve interoperability between the Software and another independently created program, on payment of applicable fee, if any. Customer shall observe strict obligations of confidentiality with respect to such information and shall use such information in compliance with any applicable terms and conditions upon which Juniper makes such information available.

**14. Third Party Software.** Any licensor of Juniper whose software is embedded in the Software and any supplier of Juniper whose products or technology are embedded in (or services are accessed by) the Software shall be a third party beneficiary with respect to this Agreement, and such licensor or vendor shall have the right to enforce this Agreement in its own name as if it were Juniper. In addition, certain third party software may be provided with the Software and is subject to the accompanying license(s), if any, of its respective owner(s). To the extent portions of the Software are distributed under and subject to open source licenses obligating Juniper to make the source code for such portions publicly available (such as the GNU General Public License ("GPL") or the GNU Library General Public License ("LGPL")), Juniper will make such source code portions (including Juniper modifications, as appropriate) available upon request for a period of up to three years from the date of distribution. Such request can be made in writing to Juniper Networks, Inc., 1194 N. Mathilda Ave., Sunnyvale, CA 94089, ATTN: General Counsel. You may obtain a copy of the GPL at <http://www.gnu.org/licenses/gpl.html>, and a copy of the LGPL at <http://www.gnu.org/licenses/lgpl.html>.

**15. Miscellaneous.** This Agreement shall be governed by the laws of the State of California without reference to its conflicts of laws principles. The provisions of the U.N. Convention for the International Sale of Goods shall not apply to this Agreement. For any disputes arising under this Agreement, the Parties hereby consent to the personal and exclusive jurisdiction of, and venue in, the state and federal courts within Santa Clara County, California. This Agreement constitutes the entire and sole agreement between Juniper and the Customer with respect to the Software, and supersedes all prior and contemporaneous agreements relating to the Software, whether oral or written (including any inconsistent terms contained in a purchase order), except that the terms of a separate written agreement executed by an authorized Juniper representative and Customer shall govern to the extent such terms are inconsistent or conflict with terms contained herein. No modification to this Agreement nor any waiver of any rights hereunder shall be effective unless expressly assented to in writing by the party to be charged. If any portion of this Agreement is held invalid, the Parties agree that such invalidity shall not affect the validity of the remainder of this Agreement. This Agreement and associated documentation has been written in the English language, and the Parties agree that the English version will govern. (For Canada: Les parties aux présentés confirment leur volonté que cette convention de même que tous les documents y compris tout avis qui s'y rattache, soient rédigés en langue anglaise. (Translation: The parties confirm that this Agreement and all related documentation is and will be in the English language)).

# Table of Contents

Client-side changes made by IVE applications.....	1
Juniper Installer Service .....	1
Package file and file location .....	2
Additional files installed by package and file locations .....	2
Windows NT and Windows 2000 .....	2
Windows XP .....	2
Files remaining after uninstall .....	3
Registry modifications .....	3
Log file location .....	3
Juniper Setup .....	3
Package files .....	3
Windows XP and Windows 2000 .....	3
Windows Vista.....	3
Additional files installed by package and file locations .....	3
Windows XP and Windows 2000 .....	3
Windows Vista.....	4
Registry modifications .....	6
Log file location.....	6
Windows XP and Windows 2000 .....	6
Windows Vista.....	6
Host Checker .....	7
Windows clients.....	7
Package file and file location .....	7
Additional files installed by package and file locations.....	7
Files remaining after uninstall .....	8
Registry modifications .....	8
Log file locations.....	9
Linux clients.....	9
Application and additional files installed by Host Checker .....	9
Files remaining after uinstall.....	9
Log files installed by Host Checker .....	9
Macintosh clients .....	9
Application and additional files installed by Host Checker .....	9
Files remaining after uninstall .....	9
Log files installed by Host Checker .....	10
Secure Virtual Workspace .....	10
Registry modifications .....	10
Files remaining after uninstall .....	10
Log file locations.....	10
Cache Cleaner .....	10
Package file and file location.....	10
Additional files installed by package and file locations .....	10
Files remaining after uninstall .....	11
Registry modifications .....	11

- Log file location..... 12
- Secure Meeting..... 12
  - Windows clients..... 12
    - Package file and file location ..... 12
    - Additional files installed by package and file locations..... 12
    - Files remaining after uninstall ..... 12
    - Registry modifications ..... 12
    - Log file locations..... 12
  - Macintosh clients ..... 13
    - Application and additional files installed by Secure Meeting..... 13
    - Files remaining after uninstall ..... 13
    - Log files installed by Secure Meeting ..... 13
  - Linux clients..... 13
    - Application and additional files installed by Secure Meeting..... 13
    - Log files installed by Secure Meeting ..... 14
- Windows Secure Application Manager (WSAM)..... 14
  - Package file and file location ..... 14
  - Additional files installed by package and file locations ..... 14
  - Files remaining after uninstall..... 15
    - Windows 2000/XP ..... 16
    - Windows 98/Millennium..... 16
  - Registry modifications ..... 16
    - Installation values ..... 16
    - Uninstallation values..... 16
    - Current Version values..... 17
    - TDI driver values (Windows 2000/XP only) ..... 17
    - Debug values ..... 18
    - Miscellaneous ..... 18
  - Log file location..... 19
- Java Secure Application Manager (JSAM)..... 19
  - Windows clients..... 19
    - Location of additional files..... 19
    - Files remaining after uninstall ..... 19
    - Registry modifications ..... 19
    - Log file locations..... 20
  - Macintosh clients ..... 20
    - Application and additional files installed by JSAM..... 20
    - Files remaining after uninstall ..... 20
    - Log files installed by JSAM ..... 20
  - Linux clients..... 20
    - Application and additional files installed by JSAM..... 20
    - Files remaining after uninstall ..... 20
    - Log files installed by JSAM ..... 20
- Network Connect and GINA..... 21
  - Windows clients..... 21
    - Package file and file location ..... 21
    - Hosts file change ..... 21
    - Additional files installed by package and file locations..... 21
    - Files remaining after uninstall ..... 22
    - Registry modifications ..... 23
    - Log file location ..... 23
  - Linux clients..... 23
    - Application and additional files installed by Network Connect.... 23
    - Files remaining after uninstall ..... 23

Log files installed by Network Connect .....	24
Macintosh clients .....	24
Application and additional files installed by Network Connect....	24
Files remaining after uninstall .....	25
Log files installed by Network Connect .....	25
Windows Terminal Services .....	25
Package file and file location .....	25
Additional files installed by package and file locations .....	25
Files remaining after uninstall .....	26
Registry modifications .....	26
Log file location .....	26
Citrix Terminal Services.....	26
Package file and file location .....	27
Additional files installed by package and file locations .....	27
Registry modifications .....	28
Files remaining after uninstall .....	28
Log file location .....	28
Required rights to run and install applications .....	28



# Client-side Changes Guide

This guide lists the package file names used by the IVE to install client-side components, files the packages install and uninstall, and registry changes they make to the user's system. It also describes the rights that are required in order to install and run various IVE client-side components. Topics in this section include:

- “Client-side changes made by IVE applications” on page 1
- “Required rights to run and install applications” on page 28

---

## Client-side changes made by IVE applications

This section describes the components that the IVE uses to install and run its client-side applications. The following descriptions include the components' names, installer locations, and log directories, as well as registry changes that the components make during installation:

- “Juniper Installer Service” on page 1
- “Juniper Setup” on page 3
- “Host Checker” on page 7
- “Secure Virtual Workspace” on page 10
- “Cache Cleaner” on page 10
- “Secure Meeting” on page 12
- “Windows Secure Application Manager (WSAM)” on page 14
- “Java Secure Application Manager (JSAM)” on page 19
- “Network Connect and GINA” on page 21
- “Windows Terminal Services” on page 25
- “Citrix Terminal Services” on page 26

### ***Juniper Installer Service***

When installing a Windows-based IVE client application on a user's Windows system, the Juniper Installer Service deploys two files on the client machine:

- JuniperSetup.ocx
- NeoterisSetupService.exe (The IVE auto-starts this service on installation, then stops and removes it on uninstall.)

### **Package file and file location**

The IVE loads the installer service files in the following locations:

- C:\Program Files\Neoteris\Installer Service Folder\NeoterisSetupService.exe
- C:\WINNT\Downloaded Program Files\JuniperSetup.ocx (Windows NT and 2000)
- C:\Windows\Downloaded Program Files\JuniperSetup.ocx (Windows XP)

### **Additional files installed by package and file locations**

#### ***Windows NT and Windows 2000***

The Juniper Installer Service installs the following files in C:\WINNT\Downloaded Program Files:

- string\_de.properties
- string\_en.properties
- string\_es.properties
- string\_fr.properties
- string\_ja.properties
- string\_ko.properties
- string\_zh.properties
- string\_zh\_cn.properties

#### ***Windows XP***

The Juniper Installer Service installs the following files in C:\Windows\Downloaded Program Files:

- string\_de.properties
- string\_en.properties
- string\_es.properties
- string\_fr.properties
- string\_ja.properties
- string\_ko.properties
- string\_zh.properties
- string\_zh\_cn.properties

**Files remaining after uninstall**

When the ActiveX control is deleted from within Internet Explorer, it leaves the following files behind:

- C:\Documents and Settings\\Application Data\Juniper Networks\Setup\JuniperSetupCtl.log
- C:\Program Files\Neoteris\Installer\_Service\NeoterisSetupService.log

**Registry modifications**

The installer package creates a registry key under HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\Neoteris Setup Service.

**Log file location**

C:\Program Files\Neoteris\Installer Service

***Juniper Setup***

When a Windows user signs in to the IVE, the IVE attempts to install an ActiveX control (Juniper Setup) on the user's system. If the IVE successfully installs Juniper Setup, Juniper Setup manages the installation of Windows-based IVE client applications.

**Package files**

The IVE loads the following installer files.

***Windows XP and Windows 2000***

- JuniperSetupSP1.cab
- JuniperSetup.exe.cab

***Windows Vista***

- JuniperSetupClient.cab
- JuniperSetupClientInstaller.exe

**Additional files installed by package and file locations*****Windows XP and Windows 2000***

The Juniper Setup installs the following files in C:\Documents and Settings\\Application Data\Juniper Networks\Setup:

- dsmmf.exe
- dsmmf.log
- dsmmfres\_de.dll
- dsmmfres\_es.dll
- dsmmfres\_fr.dll

- dsmmfres\_ja.dll
- dsmmfres\_ko.dll
- dsmmfres\_zh.dll
- dsmmfres\_zh\_cn.dll
- JuniperSetupApp.exe
- JuniperSetupApp.log
- JuniperSetupCtrl.log
- JuniperSetupDLL.dll
- JuniperSetupDLL.log
- NeoterisSetup.ocx
- setupResource\_de.dll
- setupResource\_en.dll
- setupResource\_es.dll
- setupResource\_fr.dll
- setupResource\_ja.dll
- setupResource\_ko.dll
- setupResource\_zh.dll
- setupResource\_zh\_cn.dll
- string\_de.properties
- string\_en.properties
- string\_es.properties
- string\_fr.properties
- string\_ja.properties
- string\_ko.properties
- string\_zh.properties
- string\_zh\_cn.properties
- uninstall.exe
- versionInfo.ini

#### **Windows Vista**

The Juniper Setup installs the following files in C:\Documents and Settings\\Application Data\Juniper Networks\Setup Client:

- dsmmfs.exe
- dsmmfres\_de.dll
- dsmmfres\_es.dll
- dsmmfres\_fr.dll
- dsmmfres\_ja.dll
- dsmmfres\_ko.dll
- dsmmfres\_zh.dll
- dsmmfres\_zh\_cn.dll
- JuniperExt.log
- JuniperSetupClient.exe
- JuniperSetupClient.ini
- JuniperSetupClient.log
- JuniperSetupClientDll.log
- JuniperSetupDll.dll
- JuniperSetupOCX.exe
- setupResource\_de.dll
- setupResource\_en.dll
- setupResource\_es.dll
- setupResource\_fr.dll
- setupResource\_ja.dll
- setupResource\_ko.dll
- setupResource\_zh.dll
- setupResource\_zh\_cn.dll
- string\_de.properties
- string\_en.properties
- string\_es.properties
- string\_fr.properties
- string\_ja.properties
- string\_ko.properties
- string\_zh.properties
- string\_zh\_cn.properties

- uninstall.exe

### Registry modifications

For Windows Vista, the Juniper Setup creates the following registry keys in HKEY\_CURRENT\_USER\SOFTWARE\Microsoft\Internet Explorer\Low Rights\ElevationPolicy\{3E8944DC-79B5-4650-9C2E-83885548A119}:

- String: AppName. Set to “JuniperSetupClient.exe.”
- String AppPath. Set to “\$OUTDIR”
- String Policy. Set to “3”

Additionally, the Juniper Setup creates the following registry keys in HKEY\_CURRENT\_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\\${NEO\_FULL\_NAME}:

- String DisplayName. Set to “\${NEO\_COMPANY\_NAME} \${NEO\_DISPLAY\_NAME}”
- String UninstallString. Set to “\$INSTDIR\uninstall.exe”
- String StartupApp. Set to “\$INSTDIR\JuniperSetupClient.exe”
- String StopApp. Set to “\$INSTDIR\JuniperSetupClient.exe -stop”
- String DisplayVersion. Set to “\$NEO\_SETUP\_CLIENT\_VERSION”
- String Publisher. Set to “{NEO\_COMPANY\_NAME}”
- String URLInfoAbout. Set to “http://www.juniper.net”

### Log file location

#### **Windows XP and Windows 2000**

- C:\Documents and Settings\\Application Data\Juniper Networks\

#### **Windows Vista**

- C:\Users\\AppData\Roaming\Juniper Networks\

For low-integrity processes, such as Internet Explorer 7, the ActiveX installer installs the following log files in C:\Users\\AppData\Local\Temp\Low:

- JuniperSetupClientCtrl.log
- JuniperSetupDII.log

## Host Checker

### Windows clients

To run Host Checker, the IVE downloads the `neoHCSetup.exe.cab` package to the user's client. This package is responsible for downloading additional files to the user's system in order to run Host Checker. Host Checker deletes the `neoHCSetup.exe.cab` package after installation is complete.

### Package file and file location

C:\Documents and Settings\\Local Settings\Temp\neoHCSetup.exe.cab

### Additional files installed by package and file locations

Host Checker installs the following additional files on the client:

- dsHostChecker.exe
- dsHostCheckerProxy.exe
- dsHostCheckerResource\_de.dll
- dsHostCheckerResource\_en.dll
- dsHostCheckerResource\_es.dll
- dsHostCheckerResource\_fr.dll
- dsHostCheckerResource\_ja.dll
- dsHostCheckerResource\_ko.dll
- dsHostCheckerResource\_zh.dll
- dsHostCheckerResource\_zh\_cn.dll
- dshttpcommon.dll
- dsnsisdll.dll
- dsWinClient.dll
- EPCheck.dll
- psapi.dll
- restore\_win2k.txt
- restore\_win98.txt
- uninstall.exe
- versionInfo.ini

Host Checker installs the additional files in: C:\Documents and Settings\\Application Data\Juniper Networks\HostChecker

In addition, if you implement policies that download or check for third-party software, Host Checker may install additional DLLs in sub-folders of: `C:\Documents and Settings\\Application Data\Juniper Networks\HostChecker`

For example:

- If you implement Advanced Endpoint Defense Malware Protection policies, Host Checker creates a sub-folder called `policy_x` in this directory and installs Whole Security DLLs in this folder.
- If you implement a pre-defined rule, Host Checker creates a sub-folder called `AV` and installs the DLLs needed to check for the integrated third-party software.

### **Files remaining after uninstall**

None.

### **Registry modifications**

Host Checker sets the following registry values:

- Strings: `LogFile` and `level` are set in `HKEY_CURRENT_USER\SOFTWARE\Juniper\Host Checker\Debug\dsHostChecker`
- Strings: `Language` and `InstallPath` are set in `HKEY_CURRENT_USER\SOFTWARE\Juniper\Host Checker`

Additionally, Host Checker sets the following values in `HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Neoteris_Host_Checker`:

- String: `DisplayName`. Set to "Juniper Networks Host Checker."
- String: `DisplayVersion`. Set to current product version number.
- String: `Publisher`. Set to "Juniper Networks."
- String: `QuietUninstallString`. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Cache Cleaner <version number>\uninstall.exe" /S"
- String: `StartupApp`. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\dsHostChecker.exe"
- String: `StopApp`. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\dsHostChecker.exe" -stop"
- String: `UninstallString`. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\uninstall.exe"
- String: `URLInfoAbout`. Set to "http://www.juniper.net"

**Log file locations**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console.

When you enable logging, Host Checker adds log files to the following locations:

- C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\dsHostChecker.log
- C:\Documents and Settings\\Application Data\Juniper Networks\EPCheck\EPCheck.log
- C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\dsHostCheckerProxy.log

**Linux clients****Application and additional files installed by Host Checker**

Host Checker installs \$HOME/.juniper\_networks/hostchecker.jar on the Linux client:

**Files remaining after uninstall**

The following files remain on the Linux client after uninstall:

- \$HOME/.juniper\_networks/dsHCLauncher\_linux1.log
- \$HOME/.juniper\_networks/dsHostChecker\_linux1.log

**Log files installed by Host Checker**

Host Checker installs the following log files on Linux systems.

- \$HOME/.juniper\_networks/dsHCLauncher\_linux1.log
- \$HOME/.juniper\_networks/dsHostChecker\_linux1.log

**Macintosh clients****Application and additional files installed by Host Checker**

Host Checker installs the following files on the Macintosh client:

- ~/Library/Application Support/Juniper Networks/hostchecker.jar
- ~/Library/Application Support/Juniper Networks/hcport.txt
- ~/Library/Application Support/Juniper Networks/ preauthCookie.txt

**Files remaining after uninstall**

There is no Host Checker uninstall on the Macintosh client.

**Log files installed by Host Checker**

Host Checker stores the log files in the following location on the Macintosh client:  
~/Library/Logs/Juniper Networks.

**Secure Virtual Workspace**

If you implement Secure Virtual Workspace (SVW), Host Checker downloads neoSVWData.zip and neoSVWDlls.zip. Then, Host Checker unzips the following files onto the client computer under C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\policy\_<number>:

- wallpaper.bmp
- dsjvd.dll
- dsjvdsvc.dll
- dsmonitor.dll
- dsVdeskPackage.dll

neoSVWData.zip and neoSVWDlls.zip are removed after unzipping the files.

**Registry modifications**

SVW creates the key HKEY\_CURRENT\_USER\SOFTWARE\Juniper Networks\VDesk.

**Files remaining after uninstall**

None. Host Checker uninstalls SVW as part of the Host Checker uninstallation process.

**Log file locations**

SVW adds the following log files to C:\Documents and Settings\\Application Data\Juniper Networks\Host Checker\policy\_<number>:

- dsvdPackage.log
- dsjvdsvc.log

**Cache Cleaner**

To execute Cache Cleaner, the IVE downloads the neoCacheCleanerSetup.exe.cab package to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Cache Cleaner.

**Package file and file location**

C:\Documents and Settings\\Local Settings\Temp\neoCacheCleanerSetup.exe.cab

**Additional files installed by package and file locations**

Cache Cleaner installs the following additional files on the client:

- dsCacheCleaner.exe
- uninstall.exe
- versionInfo.ini

Cache Cleaner installs the additional files in: C:\Documents and Settings\\Application Data\Juniper Networks\CacheCleaner <version number>

### Files remaining after uninstall

None

### Registry modifications

Cache Cleaner sets the following registry values in HKEY\_CURRENT\_USER\SOFTWARE\Juniper Networks\Cache Cleaner\Debug\dsCacheCleaner:

- String: LogFile
- String: level

Additionally, Cache Cleaner sets the following string registry values in HKEY\_CURRENT\_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Neoteris\_Cache\_Cleaner <version number>:

- String: DisplayName
- String: DisplayVersion. Set to the current software version.
- String: folders. Set to the folders that Cache Cleaner must clear when it is done.
- String: IVEHost. Set to the URL of the IVE.
- String: Publisher. Set to "Juniper Networks"
- String: QuietUninstallString. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Cache Cleaner\uninstall.exe" /S"
- String: StartupApp. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Cache Cleaner\dsCacheCleaner.exe"
- String: StopApp. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Cache Cleaner\dsCacheCleaner.exe" -action stop -nodelete 1"
- String: UninstallString. Set to "C:\Documents and Settings\\Application Data\Juniper Networks\Cache Cleaner\uninstall.exe"
- String: URLInfoAbout. Set to "http://www.juniper.net"

**Log file location**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console. When you enable logging, Cache Cleaner adds log files to: C:\Documents and Settings\\Application Data\Juniper Networks\CacheCleaner <version number>\dsCacheCleaner.log.

**Secure Meeting****Windows clients**

To execute the Windows version of Secure Meeting, the IVE downloads the neoCBoxSetup.exe.cab package to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Secure Meeting.

**Package file and file location**

C:\Documents and Settings\\Local Settings\Temp\neoCBoxSetup.exe.cab

**Additional files installed by package and file locations**

With an Active-X based install, Secure Meeting installs additional files in: C:\Documents and Settings\\Application Data\Juniper Networks\Secure Meeting <version number>. (See directory for a complete list of files.)

**Files remaining after uninstall**

None

**Registry modifications**

Secure Meeting sets the following registry values:

- String: Language is set in HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Meeting <version number>
- String: level is set in HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Meeting <version number>\Debug\dsCboxUI\_win

**Log file locations**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console.



**NOTE:** The maximum file size for each of the Secure Meeting log files is 10 MB.

---

When you enable logging, Secure Meeting adds log files to the following locations:

- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\dsCboxUI\_win.log -and- dsCboxUI\_win.log.old

- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\dscheckboxui\_viewer.log -and- dscheckboxui\_viewer.log.old
- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\dscheckboxui\_prsnt.log -and- dscheckboxui\_prsnt.log.old
- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\JuniperSetup.log -and- JuniperSetup.log.old
- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\JuniperSetupApp.log -and- JuniperSetupApp.log.old
- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlook.log -and- SecureMeetingOutlook.log.old
- C:\Users\\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlookApp.log -and- SecureMeetingOutlookApp.log.old

## Macintosh clients

### ***Application and additional files installed by Secure Meeting***

Secure Meeting installs the following files on the Macintosh client:

- ~/Library/Application Support/Juniper Networks/meetingAppMac.jar
- ~/Library/Application Support/Juniper Networks/cbox\_cnfg.txt
- ~/Library/Application Support/Juniper Networks/meeting.icns

### ***Files remaining after uninstall***

There is no Secure Meeting uninstall on the Macintosh client.

### ***Log files installed by Secure Meeting***

Secure Meeting installs log files in the following location on the Macintosh client:

- ~/Library/Logs/Juniper Networks/dsCboxLauncher\_mac1.log
- ~/Library/Logs/Juniper Networks/dsCboxUI\_mac1.log
- ~/Library/Logs/Juniper Networks/dsCboxUISummary\_mac1.log
- ~/Library/Logs/Juniper Networks/MacPresenter.log

## Linux clients

### ***Application and additional files installed by Secure Meeting***

Secure Meeting installs the following files on the Linux client:

- ~/.juniper\_networks/meetingAppSun.jar
- ~/.juniper\_networks/libSMJNIXWinLinux.so

**Log files installed by Secure Meeting**

- ~/.juniper\_networks/LinuxPresenter1.log
- ~/.juniper\_networks/dsCboxUISummary\_linux1.log
- ~/.juniper\_networks/dsCboxUI\_linux1.log
- ~/.juniper\_networks/dsCboxLauncher\_linux1.log

**Windows Secure Application Manager (WSAM)**

To execute WSAM, the IVE downloads the `samsetup.exe.cab` or `samsetupnt.exe.cab` package to the user's client, depending on the user's platform. These packages are responsible for downloading additional files to the user's system in order to execute WSAM.

**Package file and file location**

WSAM downloads its package files to the following locations:

- Windows 2000 and Windows XP:  
C:\Documents and Settings\\Local Settings\Temp\samsetupnt.exe.cab
- Windows 98 and Windows ME:  
C:\Documents and Settings\\Local Settings\Temp\samsetup.exe.cab



**NOTE:** You may choose to use a WSAM stand-alone installer or scriptable installer instead of the standard Web installers mentioned above. If you do, the installers are located where you save them, which may not be the same directories listed above. The file names for these downloadable installers are:

- **WSAMInst.exe**—WSAM stand-alone installer for Windows 98/ME systems
  - **WSAMInstNt.exe**—WSAM stand-alone installer for Windows 2000/XP systems
  - **SamLauncher.exe**—Scriptable WSAM installer
  - **WSAM.ppc2003\_arm.cab**—WSAM stand-alone installer for Pocket PC systems
- 

**Additional files installed by package and file locations**

WSAM installs the following additional files on the client:

- dsSamProxy.exe
- dsSamResource\_DE.dll
- dsSamResource\_EN.dll
- dsSamResource\_ES.dll
- dsSamResource\_FR.dll
- dsSamResource\_JA.dll

- dsSamResource\_KO.dll
- dsSamResource\_ZH.dll
- dsSamResource\_ZH\_CN.dll
- dsSamUI.exe
- dsWinClient.dll
- dsWinClientResource\_DE.dll
- dsWinClientResource\_EN.dll
- dsWinClientResource\_ES.dll
- dsWinClientResource\_FR.dll
- dsWinClientResource\_JA.dll
- dsWinClientResource\_KO.dll
- dsWinClientResource\_ZH.dll
- dsWinClientResource\_ZH\_CN.dll
- gaptbar.dll
- install.log
- samclean.exe
- samdiagEx.dll (Windows 2000 and Windows XP only)
- SAMNB.dll (Windows 2000 and Windows XP only)
- samnsp.dll (Windows 2000 and Windows XP only)
- samsdmon.exe (Windows 98 and Windows ME only)
- gapsp.dll (Windows 98 and Windows ME only)
- UninstallSAM.exe
- versionInfo.ini

WSAM installs the additional files in: C:\Program Files\Juniper Networks\Secure Application Manager

On Windows 2000 and Windows XP systems, WSAM also installs a TDI driver (neofltr\_< release number > \_ < build number > .sys) in \$SystemRoot\system32\drivers. (For example, for release 5.2.0.9300, WSAM installs NEOFLTR\_520\_9300.sys in C:\WINDOWS\System32\drivers\.)

### **Files remaining after uninstall**

After WSAM uninstalls, the following files remain on the client:

### **Windows 2000/XP**

- samnsp.dll
- samclean.exe

### **Windows 98/Millennium**

- gapsp.dll
- samclean.exe
- samsdmon.exe

### **Registry modifications**

WSAM sets the following registry values:

#### **Installation values**

WSAM sets the following installation values in  
HKEY\_LOCAL\_MACHINE\SOFTWARE\Juniper Networks\Secure Application Manager:

- String: InstallPath. Set to: C:\Program Files\Juniper Networks\Secure Application Manager
- String: Language. Set to: EN (or appropriate language value)

#### **Uninstallation values**

WSAM sets the following uninstall values in  
HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\Neoteris\_Secure\_Application\_Manager\Commands:

Windows 98/Millennium:

- String: RegisterLSP. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\gapsp.dll",DllRegisterServer
- String: SyncBypassList. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\gapsp.dll",SyncBypassList

Windows 2000/XP:

- String: RegisterLSP. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\samnsp.dll",DllRegisterServer
- String: SyncBypassList. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\samnsp.dll",SyncBypassList
- HKEY\_CURRENT\_USER\SOFTWARE\Neoteris\Secure Application Manager\SessionEstablishTasks
- HKEY\_CURRENT\_USER\SOFTWARE\Neoteris\Secure Application Manager\SessionCleanupTasks

**Current Version values**

WSAM sets the following uninstall and version information values in HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\Neoteris\_Secure\_Application\_Manager:

- String: DisplayName. Set to: “Juniper Networks Secure Application Manager”
- String: DisplayVersion. Set to: < *version number* > < *build number* >
- String: Publisher. Set to: Juniper Networks
- String: QuietUninstallString. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\UninstallSAM.exe
- String: StartupApp. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\dsSamProxy.exe
- String: UninstallString. Set to: C:\Program Files\Juniper Networks\Secure Application Manager\UninstallSAM.exe
- String: URLInfoAbout. Set to: <http://www.juniper.net/products/ssl>

In addition, WSAM sets the following version values:

- Location:  
HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\1  
  
Set: 1A00 to: 1
- Location:  
HKEY\_CURRENT\_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\1  
  
Set: 1A00 to: 1

**TDI driver values (Windows 2000/XP only)**

WSAM sets the following values for the TDI driver on Windows 2000 and Windows XP systems in

HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\NEOFLTR\_< *release number* > \_< *build number* > :

- String: DisplayName. Set to: Juniper Networks TDI Filter Driver (NEOFLTR\_< *release number* > \_< *build number* > )
- String: Imagepath. Set to: \C:\WINDOWS\System32\Drivers\NEOFLTR\_< *release number* > \_< *build number* > .SYS

In addition, WSAM sets the following values in

HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\NEOFLTR\_< *release number* > \_< *build number* > \Enum:

- String: 0. Set to: Root\LEGACY\_NEOFLTR\_< *release number* > \_< *build number* > \0000

- DWord: Count. Set to: 0x00000001
- DWord: NextInstance. Set to: 0x00000001

#### **Debug values**

- HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Application Manager\Debug\SamNB (For File-Sharing option only)
  - String: “LogFile”, Value: “dsSamDebug.log”
- HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Application Manager\Debug\SamUI
  - String: “LogFile”, Value: “dsSamDebug.log”
- HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Application Manager\Debug\Setup
  - String: “LogFile”, Value: “dsSamDebug.log”
- HKEY\_CURRENT\_USER\Software\Juniper Networks\Secure Application Manager\Debug\Proxy

#### **Miscellaneous**

WSAM sets the following miscellaneous registry values:

- Location: HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\WinSock2\Parameters\NameSpace\_Catalog5\Catalog\_Entries\0000000000X (where X is a number between 1 and 7). Description: WSAM creates these keys when it runs from an administrator account for the first time. These keys register the namespace provider (NSP) installed by WSAM.
- Location: HKLM\Software\Microsoft\Windows\CurrentVersion\RunServices. Key: JuniperLSPFix. Set to: \$WINDIR\rundll32.exe \$1\gapsp.dll,FixProtocolChain. Description: Enables Network Connect and WSAM to coexist on Windows 98 and Windows ME platforms.
- String: IntranetAuthOptions is set in HKEY\_LOCAL\_MACHINE\SOFTWARE\Neoteris\Secure Application Manager\Backup and HKEY\_CURRENT\_USER\SOFTWARE\Neoteris\Secure Application Manager\Backup.
- The list of LSPs ignored when running WSAM are in HKEY\_CURRENT\_USER\SOFTWARE\Juniper Networks\Secure Application Manager\AllowedLsp.

**Log file location**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console. When you enable logging, WSAM adds log files to the following location: C:\Documents and Settings\\Application Data\Juniper Networks\Secure Application Manager.

WSAM also adds an installation log file to the C:\Program Files\Juniper Networks\Secure Application Manager directory.

**Java Secure Application Manager (JSAM)**

To execute JSAM, the IVE launches an applet on the user's client. This applet handles downloading additional files to the user's system in order to execute JSAM.

In addition, JSAM modifies the hosts file if you choose **Automatic host-mapping** under **Users > User Roles > Role > SAM > Options > Java SAM Options**.

**Windows clients****Location of additional files**

JSAM installs additional files in the following location: C:\Documents and Settings\\Application Data\Juniper Networks\Java Secure Application Manager

**Files remaining after uninstall**

After JSAM uninstalls, only the log files remain on the client, as described in "Log file locations" on page 20.

**Registry modifications**

JSAM sets the following registry values:

- If you configure a standard NetBIOS application through JSAM, or you configure a custom application on port 137, 138, or 139, JSAM makes the following registry key modification on Windows XP machines (Administrator privileges required): SMBDeviceEnabled=dword:00000000 is set in the registry location: HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\NetBT\Parameters
- If you enable Outlook 5.5, 2000, or 2002 (Administrator privileges required), JSAM adds HKEY\_LOCAL\_MACHINE\Software\Microsoft\Exchange\Exchange Provider\Rpc\_Binding\_Order to the registry. (The second entry for this registry key is changed to ncacn\_http.)

The original value of this setting is:

ncalrpc,ncacn\_ip\_tcp,ncacn\_spx,ncacn\_np,netbios,ncacn\_vns\_spp

After JSAM is initially used, the value of this setting is:

ncalrpc,ncacn\_http,ncacn\_ip\_tcp,ncacn\_spx,ncacn\_np,netbios,ncacn\_vns\_spp

- If you disable the **Skip Web Proxy Registry Check** option under **Users > User Roles > Role > SAM > Options > Java SAM Options** (User read access required), JSAM sets:  
HKEY\_CURRENT\_USER\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Internet Settings\\ProxyEnable

### **Log file locations**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console. When you enable logging, JSAM adds log files to the following locations:

C:\Documents and Settings\\Application Data\Juniper Networks\Java Secure Application Manager\dsJSAM\_win0.log and dsJSAM\_win1.log

## **Macintosh clients**

### **Application and additional files installed by JSAM**

JSAM installs the following files on the Macintosh client:

- ~/Library/Application Support/Juniper Networks/NeoterisMac.jar
- ~/Library/Java/Extensions/libJNPRAuthKit.jnilib
- ~/Library/Application Support/Juniper Networks/jsam.icns
- ~/Library/Application Support/Juniper Networks/logo.gif

### **Files remaining after uninstall**

The following files remain on the Macintosh client after uninstall:

- ~/Library/Logs/Juniper Networks/Java Secure Application Manager

### **Log files installed by JSAM**

JSAM installs log files in the following location on the Macintosh client:

- ~/Library/Logs/Juniper Networks/Java Secure Application Manager

## **Linux clients**

### **Application and additional files installed by JSAM**

JSAM does not install any application files on the Linux client.

### **Files remaining after uninstall**

The only files that remain on the Linux client after uninstall are the log files (described below).

### **Log files installed by JSAM**

JSAM adds log files to the ~/juniper\_networks directory.

## Network Connect and GINA

### Windows clients

To execute Network Connect and Graphical Identification and Authorization (GINA), the IVE downloads the `NcSetup.exe.cab` package to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Network Connect and GINA.

### Package file and file location

`C:\Documents and Settings\\Local Settings\Temp\neoNCsetup.exe.cab`

### Hosts file change

A hosts file entry is added by Network Connect to support the following case:

- If, when NC connects, split tunneling is disabled and the original externally resolved hostname (the hostname the user initially connected to prior to the NC launch) resolves to another IP address against the internal DNS, the browser will redirect to a *Server not found* page, because no route is defined within the client system.
- At a graceful termination (sign-out or timeout) of the NC client connection, the hosts file is restored. If the hosts file was not restored in a prior case due to an ungraceful termination, the hosts file will be restored the next time the user launches Network Connect.

### Additional files installed by package and file locations

On Windows 98, Windows 2000, and Windows XP, Network Connect installs the following additional files on the client in the following locations. The following log files are installed in `C:\Program Files\Juniper Networks\Network Connect <version number>`:

- `dsNcAdmin.dll`
- `dsNetworkConnect.exe`
- `dsNcDiag.dll`
- `versionInfo.ini`
- `dsNcGina.dll`
- `dsNcResource_EN.dll`
- `dsNcResource_DE.dll`
- `dsNcResource_ES.dll`
- `dsNcResource_FR.dll`
- `dsNcResource_JA.dll`
- `dsNcResource_KO.dll`
- `dsNcResource_ZH.dll`

- dsNCResource\_ZH\_CN.dll
- dsWinClient.dll
- dsWinClientResource\_EN.dll
- dsWinClientResource\_DE.dll
- dsWinClientResource\_ES.dll
- dsWinClientResource\_FR.dll
- dsWinClientResource\_JA.dll
- dsWinClientResource\_KO.dll
- dsWinClientResource\_ZH.dll
- dsWinClientResource\_ZH\_CN.dll
- NCInst16.exe
- uninstall.exe
- dsNCInst64.exe
- nclauncher.exe
- setproxy.html

The following log files are installed in C:\Program Files\Juniper Networks\Common Files:

- dsNcService.exe

On Windows 2000 and Windows XP, Network Connect installs the following additional files on the client in the following locations:

The following log files are installed in c:\<WINDIR>\system32:

- dsGinaLoader.dll

The following log files are installed in c:\<WINDIR>\system32\drivers:

- dsNcAdpt.sys

On Windows 98, Network Connect installs the following additional files on the client:

The following log files are installed in C:\<WINDIR>\system:

- dsGinaLoader.dll
- dsNcAd98.sys

### ***Files remaining after uninstall***

After Network Connect uninstalls, the following files remain on the client:

- dsGinaLoader.dll
- C:\Program Files\Juniper Networks\Common Files\Config.ini

### **Registry modifications**

The HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\RunOnce is required to remain “as is” on the client or Network Connect installation and launch fails.

Additionally, if GINA is enabled in the Admin Web console, Network Connect sets following string registry value in HKEY\_LOCAL\_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon:

- String: GinaDLL. Set to “dsGinaLoader.dll”

### **Log file location**

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console.

When you enable logging, Network Connect adds log files to the following location:

C:\Documents and Settings\\Application Data\Juniper Networks\Network Connect 5.2.0

## **Linux clients**

### **Application and additional files installed by Network Connect**

Network Connect installs the following files on the Linux client:

- ~/.juniper\_networks/ncLinuxApp.jar
- ~/.juniper\_networks/network\_connect/installNC.sh
- ~/.juniper\_networks/network\_connect/libncui.so
- ~/.juniper\_networks/network\_connect/missing.info
- ~/.juniper\_networks/network\_connect/ncdiag
- ~/.juniper\_networks/network\_connect/NC.jar
- ~/.juniper\_networks/network\_connect/ncsvc
- ~/.juniper\_networks/network\_connect/version.txt
- ~/.juniper\_networks/network\_connect/xlaunchNC.sh

### **Files remaining after uninstall**

No files remain on the Linux client after uninstall, but the ~/.juniper\_networks/network\_connect/ directory does remain.

**Log files installed by Network Connect**

Network Connect installs the following log files on Linux systems:

- ~/.juniper\_networks/network\_connect/installnc.log
- ~/.juniper\_networks/network\_connect/ncsvc.log
- ~/.juniper\_networks/network\_connect/ncuijava.log
- ~/.juniper\_networks/network\_connect/ncui.log

**Macintosh clients****Application and additional files installed by Network Connect**

Network Connect installs the following files on the Macintosh client:

- /Applications/Network Connect.app
- /usr/local/juniper/nc/<IVE\_version>/ncproxyd
- /usr/local/juniper/nc/<IVE\_version>/nctun[\_tiger].kext
- ~/Library/Application Support/Juniper Networks/
- NetworkConnectMac\_de.jar
- NetworkConnectMac\_en.jar
- NetworkConnectMac\_es.jar
- NetworkConnectMac\_fr.jar
- NetworkConnectMac\_ja.jar
- NetworkConnectMac\_ko.jar
- NetworkConnectMac\_zh.jar
- NetworkConnectMac\_zh-cn.jar
- ~/Library/Application Support/Juniper Networks/
- NetworkConnectMac\_ppc.jar (PowerPC-based Macintoshes)
- NetworkConnectMac\_i386.jar (Intel-based Macintoshes)
- ~/Library/Java/Extensions/libJNPRAuthKit.jnilib
- /usr/local/juniper/nc/install/NCJarVerify.jar
- /usr/local/juniper/nc/install/installer.common
- /usr/local/juniper/nc/install/ncinstallhelper
- /usr/local/juniper/nc/install/fwk\_reference\_tool
- /usr/local/juniper/nc/install/uninstall\_nc.sh

- /usr/local/juniper/nc/install/version

### **Files remaining after uninstall**

The following files remain on the Macintosh client after uninstall:

- All files in ~/Library/Logs/Juniper Networks/Network Connect
- /usr/local/juniper/nc/install/NCJarVerify.jar
- /usr/local/juniper/nc/install/installer.common
- /usr/local/juniper/nc/install/ncinstallhelper
- /usr/local/juniper/nc/install/fwk\_reference\_tool
- /usr/local/juniper/nc/install/uninstall\_nc.sh

### **Log files installed by Network Connect**

Network Connect stores the log files in the following location on the Macintosh client: ~/Library/Logs/Juniper Networks/Network Connect.

## **Windows Terminal Services**

To execute Windows Terminal Services, the IVE downloads the Neotermsetup.exe.cab package to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Terminal Services.

### **Package file and file location**

C:\Documents and Settings\\Application Data\Juniper Networks\Juniper Terminal Services Client\Neotermsetup.exe.cab

### **Additional files installed by package and file locations**

The Windows Terminal Services client installs the following Juniper proxy files on the client:

- dsTermServ.exe
- dsTermServ.log
- dsTermServResource\_DE.dll
- dsTermServResource\_en.dll
- dsTermServResource\_ES.dll
- dsTermServResource\_FR.dll
- dsTermServResource\_JA.dll
- dsTermServResource\_KO.dll
- dsTermServResource\_ZH.dll
- dsTermServResource\_ZH\_CN.dll

- dsWinClient.dll
- dsWinClientResource\_DE.dll
- dsWinClientResource\_EN.dll
- dsWinClientResource\_ES.dll
- dsWinClientResource\_FR.dll
- dsWinClientResource\_JA.dll
- dsWinClientResource\_KO.dll
- dsWinClientResource\_ZH.dll
- dsWinClientResource\_ZH\_CN.dll
- isadmindll.dll
- restore\_win2k.txt
- restore\_win98.txt
- uninstall.exe
- versionInfo.ini

Additionally, if the user is an administrator, Terminal Services also creates the C:\Program Files\Neoteris\Juniper Terminal Services client folder and installs msrdp.ocx in the new folder.

### Files remaining after uninstall

None

### Registry modifications

The Terminal Services client adds the level REG\_SZ key to:  
HKEY\_LOCAL\_MACHINE\Software\Juniper Networks\Juniper Terminal Services Client\Debug\dsTermServ\level.

### Log file location

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console. When you enable logging, the Terminal Services client adds log files to the following location: C:\Documents and Settings\<USERNAME>\Application Data\Juniper Networks\Juniper Terminal Services Client.

## Citrix Terminal Services

To execute Citrix Terminal Services, the IVE downloads the Neocitrixsrvsetup.exe.cab package to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Terminal Services.

### Package file and file location

C:\Documents and Settings\\Application Data\Juniper Networks\Juniper Terminal Services Client\Neocitrixsrvsetup.exe.cab

### Additional files installed by package and file locations

The Citrix Terminal Services client installs the following Juniper proxy files on the client:

- dsCitrixProxy.exe
- dsCitrixProxyResource\_DE.dll
- dsCitrixProxyResource\_en.dll
- dsCitrixProxyResource\_ES.dll
- dsCitrixProxyResource\_FR.dll
- dsCitrixProxyResource\_JA.dll
- dsCitrixProxyResource\_KO.dll
- dsCitrixProxyResource\_ZH.dll
- dsCitrixProxyResource\_ZH\_CN.dll
- dsCitrixServ.log
- dsWinClient.dll
- dsWinClientResource\_DE.dll
- dsWinClientResource\_EN.dll
- dsWinClientResource\_ES.dll
- dsWinClientResource\_FR.dll
- dsWinClientResource\_JA.dll
- dsWinClientResource\_KO.dll
- dsWinClientResource\_ZH.dll
- dsWinClientResource\_ZH\_CN.dll
- uninstall.exe
- versionInfo.ini

The Citrix Terminal Services client installs the proxy files in the following locations:

- Restricted users: C:\Documents and Settings\\Application Data\Juniper Networks\Juniper Citrix Services Client
- Administrators or restricted users with installer service: C:\Program Files\Neoteris\Juniper Citrix Services Client and C:\Program Files\Citrix\icacab

### Registry modifications

The Citrix Terminal Services client adds the level REG\_SZ key to:

HKEY\_LOCAL\_MACHINE\Software\Juniper Networks\Juniper Citrix Services Client\Debug\dsCitrixServ\level

### Files remaining after uninstall

None

### Log file location

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console. When you enable logging, the Citrix Terminal Services client adds log files to the following location: C:\Documents and Settings\<USERNAME>\Application Data\Juniper Networks\Juniper Citrix Services Client.

## Required rights to run and install applications

The following tables outline the rights that are required to install and run the following IVE client-side components using the IVE’s ActiveX, ActiveX installer service, and Java mechanisms:

- “Windows Secure Application Manager (WSAM)” on page 28
- “Java Secure Application Manager (JSAM)” on page 29
- “Network Connect” on page 29
- “Terminal Services” on page 30
- “Host Checker” on page 30
- “Cache Cleaner” on page 31
- “Secure Meeting” on page 31

Where applicable, the tables contain links to topics that describe in further detail the components that the IVE uses to install and run its client-side applications.

**Table 1: Windows Secure Application Manager (WSAM)**

	ActiveX	ActiveX: Installer Service	Java	Java	
Client/Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Admin	Restricted, Power User, or Admin	Admin	Not Applicable	See “Windows Secure Application Manager (WSAM)” on page 14

**Table 1: Windows Secure Application Manager (WSAM) (Continued)**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Client/Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Windows Secure Application Manager (WSAM)” on page 14

Notes:

- Restricted users cannot use the stand-alone installer, even if they have the Juniper installer service.
- The ActiveX installer requires users to reboot their systems after an installation or upgrade.
- Users must have ActiveX components or Java enabled through their browsers to use the WSAM installers.

**Table 2: Java Secure Application Manager (JSAM)**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Client/Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
<b>JSAM</b>					
Run	Not Applicable	Not Applicable	Restricted, Power User, or Admin	User	See “Java Secure Application Manager (JSAM)” on page 19
<b>JSAM with Host File Modification</b>					
Run	Not Applicable	Not Applicable	Admin	Admin/Root	See “Java Secure Application Manager (JSAM)” on page 19
Notes				Client system asks for the administrator password when JSAM launches.	

**Table 3: Network Connect**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
Install	Admin	Restricted, Power User, or Admin	Admin	Not Applicable	See “Network Connect and GINA” on page 21
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Power User or Admin	Not Applicable	See “Network Connect and GINA” on page 21

**Table 4: Terminal Services**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
<b>Terminal Services: RDP Client</b>					
Install	Power User or Admin	Restricted, Power User, or Admin	Power User or Admin	Not Applicable	See “Windows Terminal Services” on page 25
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Windows Terminal Services” on page 25
<b>Terminal Services: ICA Client</b>					
Install	Admin	Not Applicable	Admin	Not Applicable	See “Windows Terminal Services” on page 25
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Windows Terminal Services” on page 25

**Table 5: Host Checker**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
Install	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Host Checker” on page 7
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Host Checker” on page 7

NOTE: If you implement SVW through Host Checker, note that restricted users, power users, and admins all have adequate rights to install and run SVW.



**NOTE:** If you enable the **Advanced Endpoint Defense Malware Detection** Host Checker option and enforce the policy to install the Whole Security Confidence Online software on users’ computers, be aware of the following:

- **Category 1 and Category 2 Signature Scans**—Restricted users, power users, and administrators can install and run the scanning feature in Confidence Online. The scanning feature is supported on Windows 98 SE, Windows ME, Windows NT4, Windows 2000, and Windows XP systems.
- **Behavior Blocker**—Only administrators can install and run the behavior blocker feature in Confidence Online. The behavior blocker feature is supported on Windows 2000 and Windows XP systems.

**Table 6: Cache Cleaner**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
Install	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Cache Cleaner” on page 10
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Cache Cleaner” on page 10

**Table 7: Secure Meeting**

	<b>ActiveX</b>	<b>ActiveX: Installer Service</b>	<b>Java</b>	<b>Java</b>	
<b>Action</b>	<b>Windows</b>	<b>Windows</b>	<b>Windows</b>	<b>Mac/Linux</b>	<b>More Information</b>
<b>Secure Meeting: Win32</b>					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 12
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 12
<b>Secure Meeting: Java</b>					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	User	See “Secure Meeting” on page 12
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	User	See “Secure Meeting” on page 12
<b>Secure Meeting: Outlook Plug-in</b>					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 12
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 12





Juniper *your* Net™

[www.juniper.net](http://www.juniper.net)

**CORPORATE HEADQUARTERS**

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, CA 94089 USA  
Phone 408 745 2000 or 888 JUNIPER  
Fax 408 745 2100

Juniper Networks, Inc. has sales offices worldwide.

For contact information, refer to [www.juniper.net](http://www.juniper.net).

